



- *Versatile*
- *Dome hole option available*
- *Plumbing protection*
- *Semi-transparent media tank*

FBW Series

Automatic Backwash Filters

Suitable for use with the following media:

- **Activated Carbon** For chlorine, taste and odor reduction.
- **Catalytic Carbon** For the removal of chloramines, hydrogen sulfide and VOC's.
- **Filter Ag** Low Density Sediment removal down to 40 micron
- **Filter Sand** Sediment reduction down to 20 micron
- **Birm** Iron removal when raw water has sufficient dissolved oxygen
- **Calcium Carbonate** Raises the pH of acid water and removes turbidity. Use when pH is 6.0-6.8 and hardness is less than 5 gpg.
- **Neutralizer Blend** Raises the pH when incoming water pH is less than 6.0 or hardness is greater than 5 gpg.
- **Zeolite** Sediment and suspended solids reduction.

Features:

- **Rugged Motorized Piston Control.** Heavy-duty drive motor with gear reduction box provides power to stand up to the worst iron, manganese, scale, and hardness.
- **Full Flow Bypass Valve.** Simple quarter turn of the handle takes the unit off stream. This is ideal for watering the yard or providing water while the unit is being serviced.
- **Non-corrosive Construction.** Components are stainless steel, fiberglass, and polyethylene, eliminating rust and corrosion problems.



Model Number	Media Volume cu. ft.	Service Flow Rate (GPM)			Dimensions H" x W" x D"	Pipe Size
		Backwash	Peak	Cont.		
FBW10	1.0	5	10	3	56" x 12" x 18"	3/4" & 1"
FBW15	1.5	5	11	3	64" x 12" x 18"	
FBW20	2.0	7	13	4	59" x 12" x 18"	
FBW30	3.0	10	16	5	78" x 14" x 18"	1"

NOTE 1: Add suffix "-1" if a 1" pipe size is desired. Example: FBW15-1

NOTE 2: Add suffix "DH" if a dome hole is desired. Example: FBW15-DH

